

The innovation in AWH valve technology.

VMove Series

the pneumatic actuators for butterfly valves

- continuous shaft with double bearing
- easy assembly of all additional units
- available with VMon control head
- 300,000 switching operations guaranteed
- optimised power transmission, more torque
- integrated position indicator with switch function
- holding devices for sensors including
- hygienic design with O-ring seal
- compact design, robust stainless steel construction
- swivelling metallic angular air connection



Technical Data

	VMove 0	VMove 1	VMove 2
Connection	Inner square 9,5 mm	Inner square 9,5 mm	Inner square 14 mm
Operating Pressure	Air/Spring max. 10 bar / 145 psi	Air/Spring max. 10 bar / 145 psi Air/Air max. 8 bar / 116 psi	Air/Spring max. 10 bar / 145 psi Air/Air max. 6 bar / 87 psi
Maximum torque	40 Nm	70 Nm	180 Nm
Diameter	70 mm	90 mm	130 mm
Area of application	Butterfly valves DN 10 - 20 standard Butterfly valves DN 25 - 40 (1" - 1 1/2") optional	Butterfly valves DN 25 - 100 (1" - 4") Ball valves DN 40 - 65 (1 1/2" - 2 1/2")	Butterfly valves DN 125 - 200 Ball valves DN 80 - 100 (3" - 4")



Armaturenwerk Hötensleben GmbH, Schulstr. 5 - 6, D-39393 Hoetensleben
Tel.: +49 39405 92-0, e-mail: info@awh.eu, <http://www.awh.eu>

**Enquire
now!**